



Construction Adhesives Catalog



Replaces the following PL products: PL Premium (except for FOAMS, PVC, Styrene)
PL 200 Drywall / PL400 Subfloor / PL 600 Landscaping / PL 9000
**Will not work in lieu of PL300 (FOAM board / ABS) and PL700 Tub surround

Franklin International

Distributed in Canada by:



liquid diamond

wall protection & plastic products
15715 - 116 Ave. Edmonton, AB T5M 3W1
ph: 780.489.1901 | 1.877.489.1901

GREENchoice ADHESIVES


Over 20 Years Experience in Green Building

PROFESSIONAL STRENGTH & PERFORMANCE - INTERIOR/EXTERIOR

Titebond® Heavy Duty & VOC-compliant Heavy Duty Construction Adhesive

High-strength mastics that exceed the APA's AFG-01, ASTM D3498 and ASTM C557 specifications. Versatile, waterproof, solvent-based adhesives that handle practically every job in construction, remodeling or repair. They are designed for a wide range of construction applications, including wet, frozen and treated lumber. Also ideal for metal, brick, concrete, ceramics and most large panel-type substrates. Reduces the amount of nailing and helps eliminate squeaky floors.

Cat. No.	Size	Units/Case	Ctn. Lbs.	Pallet Qty.
5261	10.5 oz. Cartridge	12	11	108
5262	29 oz. Cartridge	12	27	38
25266	Gallon Can	2	20	75
5271	VOC 10.5 oz. Cartridge	12	12	108
5272	VOC 29 oz. Cartridge	12	32	38



Replaces the following PL products: PL Premium (except for FOAMS, PVC, Styrene) PL 200 Drywall / PL400 Subfloor / PL 600 Landscaping / PL 9000

**Will not work in lieu of PL300 (FOAM board / ABS) and PL700 Tub surround

Titebond® Interior/Exterior Construction Adhesive

Specifically designed for use on most common building materials including foams, plastics and wood. Provides excellent water-resistance and works extremely well in colder temperatures. It also offers a 30-minute working time to allow precise placement of materials. It exceeds the performance requirements of ASTM C557.

3451	10.5 oz. Cartridge	12	12	108
3452	29 oz. Cartridge	12	32	38



Titebond® Panel & Foamboard Construction Adhesive

Designed for bonding foamboard insulation and polystyrene to most porous building materials. It is also ideal for use on paneling, plastics, tub surrounds, wood, fiberglass, drywall, ceramic tile, metal and more. It exceeds the performance requirements of the AFG-01 and ASTM C557 specifications.

3461	10.5 oz. Cartridge	12	11	108
3462	29 oz. Cartridge	12	29	38



Titebond® Projects & Repair Construction Adhesive

A versatile formula designed for general purpose applications of most building materials. It is safe for use on wood, drywall, ceramic, metal, plywood, hardboard and more. It exceeds the performance requirements of the AFG-01 and ASTM C557 specifications.

5321	10.5 oz. Cartridge	12	11	108
5322	29 oz. Cartridge	12	29	38



Titebond® All Weather Subfloor Adhesive

An ideal choice for subfloor installations. It is designed for particleboard, OSB, engineered lumber and wet, frozen and treated lumber. It offers a strong initial tack, provides superior strength and remains permanently flexible. Excellent durability – will not become brittle. It reduces the amount of nailing and helps eliminate squeaky floors. Offers excellent cold weather extrudability down to 0°F. It exceeds the performance requirements of AFG-01, ASTM D3498 and ASTM C557 specs.

5491	10.5 oz. Cartridge	12	11	108
5492	29 oz. Cartridge	12	29	38



Titebond® Professional Drywall Adhesive

Designed to apply drywall to wood, hardboard, gypsum wallboard, cold-rolled steel and aluminum. Its strong initial tack allows the panels to be positioned quickly without slipping. Fills irregularities and gaps in substrates, providing a strong bond and a more solid backup surface. It is unaffected by moisture and resists aging. It will not become hard or brittle with age. It exceeds the performance requirements of the ASTM C557 specification.

5352	29 oz. Cartridge	12	29	38
------	------------------	----	----	----



Titebond® Professional Tub Surround Adhesive

This waterproof adhesive offers a strong bond yet is safe on plastics and foamboard. It is specifically formulated for the installation of PVC, HIP and ABS tub surrounds. It exceeds the performance requirements of ASTM C557 and ANSI A136.1 Type I and II water-resistance specifications. It also offers a long working time that allows the precise positioning of the tub surround.

5221	10.5 oz. Cartridge	12	12	108
5212	29 oz. Cartridge	12	32	38



Titebond® Landscape Retaining Wall & VOC-compliant Landscape Retaining Wall Adhesive

Professional-strength adhesives for use on retaining and landscape walls. Specially formulated for use with concrete, wood, brick, masonry, pavers and most other common landscaping materials. Works well on dry, damp and cold surfaces and is strong enough to resist water and frost.

3131	10.5 oz. Cartridge	12	11	108
3132	29 oz. Cartridge	12	27	38
3141	VOC 10.5 oz. Cartridge	12	12	108



PROFESSIONAL CONSTRUCTION ADHESIVES

Titebond.com 1-800-347-4583 • TitebondGreenChoice.com 1-888-533-9043

Titebond® GREENchoice™ Heavy Duty Construction Adhesive

Offers superior interior and exterior strength. Its all-purpose versatility is ideal for all common building materials. It provides a strong grab, fills gaps and irregularities and will remain permanently flexible. It exceeds the performance requirements of the AFG-01 and ASTM C557 specifications.

Cat. No.	Size	Units/Case	Ctn. Lbs.	Pallet Qty.
7471	10.5 oz. Cartridge	12	14	108
7472	29 oz. Cartridge	12	36	38
7479	3.5 Gallon Pail	1	43	36



Titebond® GREENchoice™ Projects & Repair Construction Adhesive

An interior adhesive designed for general repair and installation projects. The versatile formula has a long working time for precise placement. It exceeds the performance requirements of the ASTM C557 specification.

5311	10.5 oz. Cartridge	12	13	108
5312	29 oz. Cartridge	12	35	38



Titebond® GREENchoice™ Premium Polyurethane Construction Adhesive

An advanced urethane formula for interior and exterior projects. It is the highest performing product of its kind, offering unmatched strength and durability even when bonding two non-porous materials. It offers a fast set-up time as well as a smooth bead for effortless extrusion - even in near-freezing temperatures. It exceeds the performance requirements of the AFG-01, ASTM D3498 and ASTM C557 specifications.

4221	10.5 oz. Cartridge	12	15	108
4222	29 oz. Cartridge	12	38	38



Titebond® GREENchoice™ Weatherproof Subfloor Adhesive

A professional-strength formula designed for subfloor installations and plywood use. It provides a permanent bond that remains flexible, reduces nailing and helps eliminate squeaky floors. It exceeds the performance requirements of the AFG-01 and ASTM C557 specifications.

4122	29 oz. Cartridge	12	31	38
------	------------------	----	----	----



Titebond® GREENchoice™ Professional Drywall Adhesive

Specifically designed for installing drywall and paneling to most common building materials. It offers excellent adhesion, reduces nail pops and provides a "no sag" installation. It exceeds the performance requirements of the ASTM C557 specification. Tested in accordance with E72 for racking and shearing.

7272	29 oz. Cartridge	12	37	38
------	------------------	----	----	----



Titebond® GREENchoice™ Professional Cove Base Adhesive

Designed for the quick and easy installation of rubber and vinyl cove bases. Its fast, strong grab holds materials firmly in place and eliminates sagging. It offers excellent adhesion to drywall, plaster, paint, wallpaper, paneling and ceramic tile.

3401	10.5 oz. Cartridge	12	14	108
3402	29 oz. Cartridge	12	36	38
3405	Quart Can	6	20	112
3406	Gallon Can	2	27	75
3404	4 Gallon pail	1	50	36



GREENchoice™ products were designed to achieve maximum performance with minimal impact to the environment. GREENchoice™ products are VOC-compliant, containing no ozone depleting chemicals, making it safer for you and the environment. Unlike solvent-based adhesives, they are nonflammable, emit no harmful fumes and clean up easily with water.

PROFESSIONAL CONSTRUCTION ADHESIVES

Titebond® GREENchoice™ Fast Grab FRP Adhesive

A high-quality, VOC-compliant, adhesive specifically formulated for the installation of FRP (fiber-reinforced plastic) panels. Its fast grab and bonding power greatly reduce the need for extended bracing. It is environmentally superior and contains no ozone-depleting chemicals. Unlike solvent-based adhesives, it is nonflammable, emits no harmful fumes and cleans up with water.

Cat. No.	Size	Units/Case	Ctn. Lbs.	Pallet Qty.
4056	Gallon Plastic Pail	2	25	75
4054	4 Gallon Plastic Pail	1	49	36



Titebond® Solvent Based FRP Adhesive

A versatile, high-quality adhesive designed for the installation of plywood, tileboard, FRP, pre-finished hardboard, gypsum wallboard and other paneling materials. It exceeds the ASTM C557 specification. It provides excellent water-resistance and remains permanently flexible. It is easy to trowel and offers a 30-minute working time to allow precise placement of the working materials.


3222	29 oz. Cartridge	12	32	38
3227	5 Gallon Metal Pail	1	56	36



Titebond® GREENchoice™ Acoustical Ceiling Tile Adhesive

Designed for the safe and easy installation of acoustical ceiling tiles. Its fast, strong grab holds materials firmly in place and eliminates sagging. It offers excellent adhesion to common surfaces such as drywall, plaster and paint. It is environmentally superior and contains no ozone-depleting chemicals. It is nonflammable, emits no harmful fumes and cleans up with water. It also remains flexible and is unaffected by moisture.

2706	Gallon Plastic Pail	2	26	75
2704	4 Gallon Plastic Pail	1	51	36



Titebond® Trowelable Multi-Purpose Construction Adhesive

A versatile, high-quality adhesive designed for the installation of plywood, tileboard, FRP, pre-finished hardboard, gypsum wallboard and other wall-paneling materials. It also offers excellent strength on masonry, ceramics, foamboard and most rigid plastics. It provides excellent water-resistance and remains permanently flexible. It is easy to trowel and offers a 30-minute working time to allow precise placement of materials.

5156	Gallon Can	2	23	75
5157	5 Gallon Plastic Pail	1	56	36



Titebond® Fast Dry Contact Cement

A professional-quality, flammable adhesive for bonding decorative laminates, veneer, hardboard, leather, rubber and flexible metal to most common building materials. Its solvent-based formula offers superior strength and excellent aging qualities. It becomes completely dry within 10 to 15 minutes of application. It has a strong initial tack that allows immediate machining and is resistant to water, oil and heat. It spreads easily and can be applied by roller, brush or trowel.

5185	Quart Can	6	13	112
5186	Gallon Can	2	16	90



Titebond® Post-forming Neoprene Plus Contact Cement

A high-quality, fast drying, heat resistant adhesive that allows post-forming, and bonds decorative laminates, veneer, hardboard, leather, rubber and flexible metal to most common building materials. It offers a high-strength, immediate bond, that allows for immediate machining. It is environmentally superior and contains no ozone-depleting chemicals. Unlike solvent-based contact cements, it is nonflammable, VOC-compliant, has no offensive odor and cleans up with water. Neoprene Plus is the ideal choice in response to local fire codes, insurance requirements and general risk of fire.

3555	Quart Can (Clear)	6	16	112
3556	Gallon Can (Clear)	2	20	75
4635	Quart Can (Blue)	6	16	112
4636	Gallon Can (Blue)	2	20	75



Titebond® Multi-Purpose Flooring Adhesive

Titebond Solvent Free Multi-Purpose Flooring Adhesive is designed for the installation of conventional carpet, vinyl composition tile, sheet vinyl and resilient flooring. It offers a moderately slow tack and longer open time to allow for more precise flooring installations. This formula provides a professional-strength bond that is highly water-resistant. It also contains no ozone-depleting chemicals, is nonflammable, emits no harmful fumes and cleans up with water.

5115	Quart Can	6	17	112
5116	Gallon Can	2	22	75
5114	4 Gallon Pail	1	44	36



Distributed in Canada by:



liquid diamond

wall protection & plastic products
15715 - 116 Ave. Edmonton, AB T5M 3W1
ph: 780.489.1901 | 1.877.489.1901

PROFESSIONAL SPECIALTY AD

Titebond.com 1-800-347-4583 • TitebondGreenCho